SecuRite CUPBOARD LOCK

23/29/**32**/35mm WITH DIMPLE KEY





FEATURES:

- Specially designed for cupboard wooden doors having thickness of 23/29/32/35mm
- 20mm long latch for additional safety
- Precision click action locking mechanism
- Non-magnetic and rivet-less stainless steel cover

SPECIFICATIONS:

ITEM	ITEM CODE	SIZE(mm)	FINISH	PCS./SET	MRP* (₹)
SecuRite Cupboard Lock (with Dimple Keys)	P-SRC-23D	23 mm	BS	Each	578
	P-SRC-23D-S10	23 mm	BS	Set of 10	5776
	P-SRC-29D	29 mm	BS	Each	586
	P-SRC-32D	32 mm	BS	Each	592
	P-SRC-35D	35 mm	BS	Each	598

^{*}Subject to change without prior intimation

BS: Brushed steel



SecuRite CUPBOARD LOCK

23/29/32/35mm WITH DIMPLE KEY



shee in

FITTING INSTRUCTIONS:

- 1. Align the marker (Top Flap) along the panel edge.
- 2. Mark the center point of the circle.
- 3. Drill Ø21mm hole.
- 4. Insert lock through the hole from the inner side of the panel.
- 5. Secure the lock onto the inner side of the panel by using the wood screws.
- 6. Fix the bezel in the front panel to cover the drilled hole.
- 7. Fix the locking bracket on the inner side of the top panel.







